



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089

NTE1578 Integrated Circuit FM Mixer/IF Amp

Description:

The NTE1578 is an FM front-end integrated circuit in a 16-Lead DIP type package designed for use in car radio and home stereo applications. This device has a built-in AGC driver circuit which improves interference characteristics. It thereby offers advantages such as improved interference characteristics without sacrificing usable sensitivity and the conventional DX-LOCAL change-over switch.

Features:

- Double-Balanced Type MIX (Improved Spurious Characteristic)
- Keyed AGC/Keyed Classical AGC (Improved Intermodulation, Cross Modulation Characteristic)
- Differential IF Amplification (Improved Limiting Characteristic)

Absolute Maximum Ratings: ($T_A = +25^{\circ}\text{C}$ unless otherwise specified)

Maximum Supply Voltage (Pin12, Pin15), $V_{CC1\text{max}}$	8.5V
Maximum Supply Voltage (Pin5, Pin6), $V_{CC2\text{max}}$	16V
Allowable Power Dissipation ($T_A \leq +50^{\circ}\text{C}$, Note 1), $P_{D\text{max}}$	600mW
Operating Temperature Range, T_{opg}	-20° to $+70^{\circ}\text{C}$
Storage Temperature Range, T_{stg}	-40° to $+125^{\circ}\text{C}$

Note 1. $P_{D\text{max}} = 460\text{mW}$ at $T_A = +70^{\circ}\text{C}$

Recommended Operation Condition: ($T_A = +25^{\circ}\text{C}$ unless otherwise specified)

Recommended Supply Voltage (Pin12, Pin15), V_{CC1}	8V
Recommended Supply Voltage (Pin5, Pin6), V_{CC2}	13V

Electrical Characteristics: ($T_A = +25^{\circ}\text{C}$, $V_{CC1} = 8\text{V}$, $V_{CC2} = 13\text{V}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Dissipation Current	I_{CC1}	Pin 12, 15	17	25	36	mA
	I_{CC2}	Pin 5, 6	5	8	11	mA
Local OSC Input Offset	ΔV_{INOSC}		-20	0	20	mV
MIX Input Offset	ΔV_{INMIX}		-20	0	20	mV
MIX Output Offset	$\Delta I_{\text{OUT MIX}}$		-600	0	600	μA
High Level AGC Output	$V_{\text{AGC H}}$	$V_i = 0\text{dBu}$, $V_{\text{CL}} = 4\text{V}$	7.6	7.9	-	V
Low Level AGC Output	$V_{\text{AGC L}}$	$V_i = 100\text{dB}$, $V_{\text{CL}} = 4\text{V}$	-	0.5	1	V

Electrical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$, $V_{CC1} = 8\text{V}$, $V_{CC2} = 13\text{V}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
AGC Control Input	V_{CL7}	$V_i = 100\text{dBu}$, $V_{AGC} = 7\text{V}$	–	0.35	0.6	V
	V_{CL2}	$V_i = 100\text{dBu}$, $V_{AGC} = 2\text{V}$	1.2	1.7	2.2	V
IF Input Resistance	R_{IN}		230	330	430	ohm
Voltage Gain	VG	$V_i = 62\text{dBu}$	80	85	90	$\text{dB}\mu$
Input Limiting Voltage	$V_{i\text{lim}}$	$V_{AGC} = 2\text{V}$	62	71	80	$\text{dB}\mu$
AGC Input Voltage	$V_{i\text{AGC}}$	$V_{AGC} = 2\text{V}$	62	71	80	$\text{dB}\mu$
Saturation Output Voltage	V_{OUT}	$V_i = 100\text{dB}\mu$	91	95	–	$\text{dB}\mu$

Pin Connection Diagram

